



HOW TO SPECIFY WIRED RITE SYSTEMS™, INC.

SWITCH SYSTEM

- The switch panel shall be manufactured to fit integrally with the dashboard of the vehicle (unless a different location is specified by the customer).
- The switch system shall include a magnetic circuit breaker. The circuit breakers shall not reset unless the overload has been corrected.
- The option for mounting switches vertically or horizontally shall be available.
- The wiring of the vehicle shall not include fuses, relays, solenoids, or thermal circuit breakers for individual circuits.
- The back-lighting shall have two levels of intensity. The low level lights shall be activated when the vehicle lights or the ignition switch are turned on. The high level shall be activated when the individual switch is turned on. The circuitry shall be on a printed circuit board. The lights shall be the solid state type and shall have a 100,000 hour life span. The option to have each of the lights “blink” shall be available.
- The rear of the back-lighting circuit board shall be insulated either by conformal coating or foam tape.
- The back-lighting panel shall be wired with 4 feet of 2 conductor, jacketed cable. This cable is to be secured to the panel by a strain relief.
- 3/4” center to center spacing of the backlit legends is required, allowing for more switches to be mounted in a given location.
- Each switch position shall be labeled with the exact wording requested by the customer on a rear-installed, flush-mounted, engraved legend. Legends which are affixed to the panel by any adhesive is not acceptable.
- The switch panel shall be supplied by: **Wired Rite Systems™, Inc.**, 5793 Skylane Blvd., Windsor, CA. Phone: (Toll Free) 1-800-538-RITE, (Toll Free Fax) 1-800-525-RITE.
- The switch panel shall carry a 100% lifetime warranty with Wired Rite Systems™, Inc.

— SPECIFICATIONS ARE AVAILABLE FOR ADDITIONAL WIRED RITE™ PRODUCTS —